

DERWENT-ACC-NO: 1991-019969

DERWENT-WEEK: 199103

COPYRIGHT 2006 DERWENT INFORMATION LTD

TITLE: Gate structure for MOSFET - includes silicon-rich oxide
buffer layer between gate insulation and gate electrode

PATENT-ASSIGNEE: ANONYMOUS [ANON]

PRIORITY-DATA: 1990RD-0320069 (November 20, 1990)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES MAIN-IPC		
RD 320069 A	December 10, 1990	N/A
000 N/A		

INT-CL (IPC): H01L000/01

ABSTRACTED-PUB-NO: RD 320069A

BASIC-ABSTRACT:

An a MOSFET device, an Si-rich oxide layer (16) is interposed between gate insulation layer (14) and metal (silicide) gate electrode layer (18).

ADVANTAGE - The intermediate layer serves as a buffer between the gate insulation and gate electrode and minimises degradation of the insulation layer by the metal (silicide), without affecting threshold voltage; enhancement or depletion mode FETs can be made without channel implantation and in partic. a depletion mode device operating at low temp. can be fabricated

TITLE-TERMS: GATE STRUCTURE MOSFET SILICON RICH OXIDE BUFFER LAYER
GATE

INSULATE GATE ELECTRODE

DERWENT-CLASS: L03 U12

CPI-CODES: L04-C11C; L04-C12A; L04-E01B1;

EPI-CODES: U12-D02A; U12-E02;

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C1991-008766

Non-CPI Secondary Accession Numbers: N1991-015199

